


CERMIPRIM RAPID

ADHESION PRIMER FOR NEW WORK AND RENOVATION – CLOSED AND MODERATELY POROUS SUBSTRATES



Pink liquid with light sand content



DESCRIPTION

Versatile primer for low- and medium-porosity and closed media. CERMIPRIM RAPID is fast drying, so site downtime is reduced. It contains sand for optimized grip.

ADVANTAGES

- Improves mortar adhesion
- Easy and quick to apply
- Application on primer/epoxy coating, even unhandled
- Fast drying
- Single-component
- Ready to use
- Solvent-free


WHERE TO USE

Closed and moderately porous **SUBSTRATES** as defined by the relevant building codes (DTU/CPT in France).

	INTERIORS	
	WALLS	FLOORS
Concrete	x	x
Cement coatings	x	x
Heated floors		x
Parquet and wood floors (French classes CTBH, CTBX, OSB3)	x	x
Tile	x	x
Semi-flexible plastic tiles		x
Polyester coverings		x
Traces of glue		x
Asphalt screed		x
Floor paint		x
Floor resins		x
Barriers against rising damp like CER-MIBLOC		x
Other substrates	Contact us for information	

HOW TO USE

Note: The following is a typical description of application. If your site has other parameters, contact our Technical Department.



Application temperatures



Clean with water

Foot traffic 30 min

PREPARATION STEPS

For renovation, depending on the work or finish to follow, test to confirm good adhesion on the existing covering, according to the relevant building code (CPT in France).

TOOLS

Roller or flat brush.

SURFACE PREPARATION

The surface should be sound, clean, solid, free of dust, not leach moisture, rough, and be free of form oils and poorly adherant materials. To achieve this, scrape, brush, remove dust, clean, etc., and reseal if necessary.

Make the necessary repairs after, for instance, having removed any unsound tiles.

Sand paint or varnish to roughen and remove unsound paint.

Make sure wood is stable and that panels and slats are attached by screws.

PRODUCT PREPARATION

Mix before use.

APPLICATION

How to apply the primer

Apply using a roller or a flat brush in a regular, thin coat.

How to apply on a rising damp barrier primer

CERMIPRIM RAPID can be applied as a substitute for sand on the second coat of CERMIBLOC, 24 hr after it dries.

FINISH

Levelling screed or mortar must be applied on a dry product and at most 24 hr after applying the primer and without foot traffic in the room.



APPLICATION CONDITIONS

Make sure the area is dry and draught-free.

Application temperature: 5-35°C

Drying time⁽¹⁾: approximately 30 minutes.

Protect the application area from rain, frost and high temperatures

⁽¹⁾ Values obtained at 23°C and 50% RH in the laboratory. Drying times are shorter at higher temperatures and longer at lower temperatures.

CLEANING AND MAINTENANCE

Clean tools with water immediately after use, before they dry.

COMMENTS

Do not use on highly porous substrates.

TECHNICAL CHARACTERISTICS

APPARENCE – COMPOSITION

Aqueous synthetic copolymer emulsion, pigments, specific admixtures and carbonate and silica sand fillers.

COVERAGE

200 to 300 g/m² depending on the nature and roughness of the substrate

TECHNICAL CHARACTERISTICS

Non-flammable

Density: 1.5

PACKAGING

8 kg bucket: 90 per pallet

15 kg pail: 48 per pallet

STORAGE & SHELF LIFE

Storage & shelf life: 1 year in the original packaging, protected from frost and sunlight.

SAFETY INSTRUCTIONS

- EMISSIONS IN INDOOR AIR (1): Information on the level of volatile substances emitted in air indoors, presenting a toxicity risk by inhalation, on a classification scale ranging from A+ (very low emissions) to C (high emissions).
- Consult the safety data sheet at www.quickfds.fr or simply ask CERMIX France for it.
- Always wear personal protective equipment that meets current guidelines and regulations.
- Dispose of the contents and container in accordance with local/regional/national/international regulations.



We reserve the right to update this technical document. It is the user's responsibility to always check whether there is a more recent version available at our website, www.cermix.com. It is the responsibility of the person using the products to ensure that the products are compatible and suitable for the planned use. Prior tests may be carried out to confirm that products behave as expected.