


CERMICLEAN

SURFACE DEGREASER – CLEANING PRODUCT



 Transparent



DESCRIPTION

Transparent liquid for application to surfaces to be cleaned.

ADVANTAGES

- Ready to use
- Powerful surface degreaser
- Fast and easy to use


WHERE TO USE

For removing grease from the surface of the covering:

- Interior and exterior floors and walls
- Ceramic coverings, natural stone, enamel

HOW TO USE

Note: The following is a typical description of application. If your site has other parameters, contact our Technical Department.



Application temperature



Clean with water

TOOLS

Nylon scrubbing brush, paint brush, scrubbing sponge, or similar

SURFACE PREPARATION

Cover up surfaces that should not be treated before starting the work. Clean the surface: Scrape/Sweep/Vacuum. Be careful not to damage the coating.

APPLICATION

1. Apply the liquid to the surface using one of the brushes. Leave to act for about 20-30 min.
2. Scrub or rub with a scrubbing brush or scrubbing sponge for a few minutes.
3. Rinse well with warm or hot water before it dries.
4. Leave it to dry or wipe with a soft cloth.
5. As needed, return to step 1 and repeat.

APPLICATION CONDITIONS

The application temperature should be between 5 and 30°C (ideally 10 to 25°C), avoiding rain and direct sunlight.

CLEANING AND MAINTENANCE

Clean tools with water.

COMMENTS

The product is ready to use. Do not dilute. Protect surfaces that have already been treated.

The result depends on how thorough the treatment is.

Treatment will improve the area's state. There may be a difference between a site cleaned normally and a site cleaned in this way.

Check the outcome on a small area before using the product everywhere.

To remove epoxy residue, use EPONET. To clean cement residue, use CERMINET.

TECHNICAL CHARACTERISTICS

APPEARANCE - COMPOSITION

Transparent liquid containing sodium hydroxide.

COVERAGE

About 200 ml/m² per application depending on the amount of residue being removed.

TECHNICAL CHARACTERISTICS

pH>13

Density 1.05

PACKAGING

1 litre bottle. 6 bottles per box.

96 boxes per pallet, i.e. 576 bottles per palette.

STORAGE & SHELF LIFE

24 months in a dry place, protected from frost and direct sunlight.

SAFETY INSTRUCTIONS

- EMISSIONS IN INDOOR AIR (1): Information on the level of volatile substances emitted in air indoors, presenting a toxicity risk by inhalation, on a classification scale ranging from A+ (very low emissions) to C (high emissions).
- Consult the safety data sheet at www.quickfds.fr website or ask CERMIX France for it.
- Always wear personal protective equipment that meets current guidelines and regulations.
- Dispose of the contents and container in accordance with local/regional/national/international regulations.

We reserve the right to update this technical document. It is the user's responsibility to always check whether there is a more recent version available at our website, www.cermix.com. It is the responsibility of the person using the products to ensure that the products are compatible and suitable for the planned use. Prior tests may be carried out to confirm that products behave as expected.